

TECHNICAL SPECIFICATIONS SHEET

HOMERE

FEATURES



COMPACT DESK WITH A SLIDING AND ROTATABLE WORKTOP

SHELL / DRAWER / SHELF	<p>Construction: Melamine covered particle board panels, THK 19 mm, 2 sides treated with an anti-reflective coating, Brunswick oak finish. Flat edge banding, 2 mm thick glued ABS in a matching finish.</p> <p>Panel density 650 kg/m³</p> <p>Panels are sourced from sustainably managed forests (PEFC). Rated M3 fire-resistant (combustible, moderately flammable) in compliance with standard NF EN 13501-1. Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and comply with standard NF EN 717-2.</p> <p>Shell / Back panel:</p> <ul style="list-style-type: none"> - Shell mounted on 4 castors ø 40 mm (2 are lockable). - Castor colours: 2 grey roller bands and black castor shell. - Castors suitable for use on all floor types, affix to the base of the unit using steel plates and wood screws. - Half-height modesty panel H. 380 mm (reaching the shelf in its lowest position). <p>Drawer:</p> <ul style="list-style-type: none"> - Front and back panels made from THK 19 mm melamine covered particle board, in Brunswick oak (front panel) and light grey (back panel) finish. Front panel height 130 mm. Drawer usable dimensions: W. 800 x H. 80 x D. 345 mm - Metal drawer sides in an aluminium grey finish. - Drawer mounted on runners. - Hand grip to the underside of the drawer. <p>Shelf:</p> <ul style="list-style-type: none"> - Adjustable shelf (2 positions): 330 or 230 mm opening beneath the shelf.
DESK WORKTOP AND LEGS	<p>Construction: Melamine covered particle board panels, THK 25 mm, 2 sides treated with an anti-reflective coating, in a white finish. Flat edge banding, 2 mm thick glued ABS in a matching finish.</p> <p>Panel densities 650 kg/m³ to 710 kg/m³</p> <p>Panels are sourced from sustainably managed forests (PEFC). Rated M3 fire-resistant (combustible, moderately flammable) in compliance with standard NF EN 13501-1. Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and comply with standard NF EN 717-2.</p> <p>Worktop / Legs:</p> <ul style="list-style-type: none"> - Sliding and rotation of the worktop is possible thanks to a ø 220 mm metal disc affixed to the top of the storage unit, combined with two metal runners affixed to the underside of the worktop. Low friction strips facilitate movement. - Leg mounted on 2 castors ø 40 mm (both lockable). - Castor colours: 2 grey roller bands and black castor shell. - Castors suitable for use on all floor types, affix using M8 screws. - Vertical modesty panel 200 mm wide, ensuring squaring of the worktop to the panel leg.
CONFIGURATIONS	<p>Configurations: 3 positions</p> <ul style="list-style-type: none"> - Closed worktop: 100 mm gap between the vertical panel and the side of the unit. - Aligned sliding worktop: 700 mm opening to accommodate an office chair. - Rotatable worktop up to max. 90° angle: 700 mm opening to accommodate an office chair.
ASSEMBLY	<p>Self-assembly furniture (5 packages).</p> <p>Assembly of the storage unit and the worktop using screws, cam locks and dowels.</p>



DIMENSIONS

OVERALL DIMENSIONS (in mm)	
CLOSED WORKTOP CONFIGURATION	
Depth	500
Width	1020
Height	735
Height of unit excluding worktop	693

ALIGNED WORKTOP CONFIGURATION	
Depth	500
Width	1615
Height	735

90° WORKTOP CONFIGURATION	
Depth	1125
Width	1070
Height	735

